

Rillenkugellager einreihig 3002-DC-NICE - 3002-DC-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/3002-dc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN		
BORE						d (in)	O.D. D (in)
						+0.005 (mm)	+0.000 (mm)
						+0.13	+00
						-0.000	-0.013
						-0.00	-0.013
3002™	DC					0.2500	0.5675
						6.350	17.463

WIDTH B (in)	BASIC LOAD RATINGS		WEIGHT W (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lbs)	STATIC Co (lbs)		da min (in)	Da max (in)	r max (in)
0.2500 (6.350)	255 (1135)	170 (757)	0.02 (0.01)	0.330 (8.38)	0.614 (15.60)	0.012 (0.30)

Width for sealed versions = 0.3125 (7.938) Weights given are for greased and sealed versions
3008 and larger +0.000/-0.006 (-0.000/-0.15)

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558004
Innendurchmesser	6.35 mm
Innendurchmesser	1/4" inch
Außendurchmesser	17.463 mm
Außendurchmesser	11/16" inch
Dicke	6.35 mm
Dicke	1/4" inch
Gewicht	10 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE