

# Rillenkugellager einreihig 3005-DC-NICE - 3005-DC-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/3005-dc-nice>

**3000 Series® Semi-Ground Radial Bearings** **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3005™	DC					+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.013 -0.013

BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lbs) (N)	W <sup>⓪</sup> (lbs) (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)	
0.3125 7.938	350 1558	300 1355	0.04 0.02	0.503 12.78	0.778 19.76	0.012 0.30

<sup>⓪</sup> Weights given are for greased and sealed versions  
<sup>⓪</sup> 3038 and larger +.0000/-0.005 (-.000/-0.13)

## PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558158
Innendurchmesser	7.938 mm
Außendurchmesser	23.02 mm
Dicke	7.938 mm
Gewicht	20 g
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE