


Rillenkugellager einreihig 3005-SS-NICE - 3005-SS-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/3005-ss-nice>

3000 Series® Semi-Ground Radial Bearings **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- W/LOW RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|------------------------------------|-------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3005™ | | | | SS | | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.013 -0.013 |

| WIDTH B (in) (mm) | BASIC LOAD RATINGS | | WEIGHT W (lb) (kg) | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|-----------------------------|-----------------------------|-----------------------------|--------------------------------|------------------------|-----------------------|
| | DYNAMIC C (lb) (N) | STATIC Co (lb) (N) | | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.3125 7.938 | 350 1558 | 300 1335 | 0.04 0.02 | 0.503 12.78 | 0.778 19.76 | 0.012 0.30 |

Ⓜ Weights given are for greased and sealed versions
Ⓜ 3038 and larger +.0000/-0.005 (+.000/-0.13)

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | NICE |
| N° Ean13 | 3663952558189 |
| Innendurchmesser | 7.938 mm |
| Außendurchmesser | 23.02 mm |
| Dicke | 7.938 mm |
| Gewicht | 20 g |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE