


Rillenkugellager einreihig 3005-NS-NICE - 3005-NS-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/3005-ns-nice>

3000 Series® Semi-Ground Radial Bearings **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +0.005 +0.13 -0.000 -0.00	O.D. D (in) (mm) +0.000 +0.00 -0.013 -0.013
3005™					NS	0.3125 7.938	0.9063 23.020

WIDTH B (in) (mm) +0.005 +0.00 -0.005 -0.13	BASIC LOAD RATINGS		WEIGHT W (lb) (kg) 0.04 0.02	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N) 350 1558	STATIC Co (lb) (N) 300 1335		da min (in) (mm) 0.503 12.76	Da max (in) (mm) 0.778 19.76	r max (in) (mm) 0.012 0.30
0.3125 7.938	350 1558	300 1335	0.04 0.02	0.503 12.76	0.778 19.76	0.012 0.30

Ⓜ Weights given are for greased and sealed versions
Ⓜ 3038 and larger +0.000/-0.006 (+0.00/-0.15)

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558196
Innendurchmesser	7.938 mm
Außendurchmesser	23.02 mm
Dicke	7.938 mm
Gewicht	20 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE