

Rillenkugellager einreihig 3040-SS-NICE - 3040-SS-NICE

https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/3040-ss-nice

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 -0.013
3040™				SS		0.8750 22.225	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5625 14.285	1480 6598	1350 6008	0.29 0.13	1.113 28.27	1.760 44.70	0.035 0.89

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +0.0005/-0.005 (+0.001/-0.13)

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952558882
Innendurchmesser	22.225 mm
Innendurchmesser	7/8" inch
Außendurchmesser	50.8 mm
Außendurchmesser	2" inch
Dicke	14.288 mm
Dicke	9/16" inch
Gewicht	130 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE