


Rillenkugellager einreihig 7518-DL-NICE - 7518-DL-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/7518-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 3000 - 5000 RPM
- THROUGH HARDENED BEARING STEEL
- POLISHED FINISH
- WIDE RETAINER STANDARDS
- DOUBLE SEALED VERSIONS
- SPECIAL OPERATING TEMPERATURE RANGE WITH THERMALLY STABLE BALLS
- AVAILABLE IN SINGLE OR DOUBLE END SEALS
- ALL BEARINGS HAVE 3 RING AND COUPLER HOLES FOR MOUNTING TO AN APPLICATION
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK AND VIBRATION ARE CONCERNS



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7518™	+0.000 -0.005 -0.015	+0.000 -0.005 -0.015	+0.000 -0.005 -0.015	0.025 1.59	0.8750 22.23	1.872 42.47
	1.1250 28.58	2.2425 56.99	0.7500 19.05			

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	R (in) (mm) Radius	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.190 4.83	0.065 1.65	2.7806 70.25	0.035 0.89	5360 23852	2620 11659	0.80 0.36	1.375 34.93	2.312 58.72	0.036 0.89

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7514™ and larger is +0.000/-0.005 (+0.000/-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of FSC Nide® Bearings.

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473325
Innendurchmesser	28.58 mm
Außendurchmesser	65.09 mm
Dicke	19.05 mm
Gewicht	360 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE