

Rillenkugellager einreihig 5327-V-NICE - 5327-V-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/5327-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5327™	V	0.550 12.70	1.569 38.10	0.447 11.35	0.092 1.87	1.858 42.06	0.125 3.18	0.531 13.49
		+0.005/-0.000 +13/-00	+0.005/+0.000 +18/-00	+0.010/-0.010 +25/-25				+0.010/-0.010 +25/-25

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)	
17	3/16 4.75	0.16 0.07	492 2189	342 1522	226 1050	130 846	132 587	92 409

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952560281
Innendurchmesser	12.7 mm
Außendurchmesser	38.1 mm
2nd Außendurchmesser	42.06 mm
Dicke	11.35 mm
2. Dicke	13.49 mm
Gewicht	70 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE