

Rillenkugellager einreihig 5281-V-NICE - 5281-V-NICE

https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/5281-v-nice

5000 Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5281™	V	0.500 12.70	1.539 40.08	0.515 13.08	0.140 3.56	1.887 42.85	0.234 5.94	0.809 15.47
		+0.005/-0.000 +13/-00	+0.005/+0.000 +18/-00	+0.010/-0.010 +25/-25				+0.010/-0.010 +25/-25

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (lbs) (%)	100 (lbs) (%)	200 (lbs) (%)	300 (lbs) (%)	600 (lbs) (%)	1200 (lbs) (%)	
12	1/4 6.35	0.23 0.10	535 2381	367 1633	258 1148	206 917	144 641	100 445

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952560298
Innendurchmesser	12.7 mm
Außendurchmesser	40.08 mm
2nd Außendurchmesser	42.85 mm
Dicke	13.08 mm
2. Dicke	15.47 mm
Gewicht	100 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE