

Rillenkugellager einreihig 609-V-NICE - 609-V-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/609-v-nice>

600 Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS RISE OF METAL-LAYERS
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE

BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
609™	V	1.000 25.40	1.075 27.31	1.79 45.70	.630 16.00	12 3/8	0.30 9.53

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10 (lbs) (N)	50 (lbs) (N)	100 (lbs) (N)	250 (lbs) (N)	500 (lbs) (N)	1000 (lbs) (N)
1706 7562	1378 6132	1017 4520	551 2452	398 1771	284 1264

Notes
Balls - Carbon Steel Grade 52100
Washers - Carbon Steel Case Hard
Bands - Carbon Steel Soft
Bearings Oiled with a Rust Preventative
All Bearings Marked on Band with "Designation Nice USA" as Shown

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3663952560434
Innendurchmesser	25.4 mm
Außendurchmesser	50.8 mm
Dicke	16 mm
Gewicht	140 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE