

Zubehör

7608-DL-NICE - 7608-DL-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/gehauselager/zubehor/7608-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring NICE™

- PRECISION GRINDING ON ALL CONTACT SURFACES - OPTIMUM TO THE "SHRIMP-EYE" DESIGN
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- TIMEDUR HARDENED
- STEEL BEARING
- STYLISH CASE STANDARD
- SHRIMP-EYE BEARING
- EXCELLENT APPARENT ANGLE OF CONTACT
- AVAILABLE SINGLE BEARER OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP-FULL COATING - THIS WILL ENHANCE LIFE IN OILY ENVIRONMENTS
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE VIBRATION AND SHOCK ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7608™	.5000 12.70	1.7500 44.50	0.6250 15.88	0.0625 1.59	1.0000 25.40	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lbf) (N)	Static C _s (lbf) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.992 50.60	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2096 11548	1025 4561	0.36 0.16

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nide® Bearings.

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473394
Innendurchmesser	12.7 mm
Außendurchmesser	25.63 mm
Dicke	15.88 mm
Gewicht	160 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE