

Zubehör

7612-DL-NICE - 7612-DL-NICE

<https://www.123kugellager.ch/kugellager-gehauselager/gehauselager/zubehor/7612-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE™**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE 7TH DECIMAL
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- THERMALLY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHRINK MOUNTED BEARING
- EXCELLENT APPLICABLE SINGLE LIP CONTACT SURF.
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET EDGE. THIS WILL ELIMINATE AS AN OPTION.
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE HEATING AND VIBRATION ARE NOT EXPECTED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7612™	.7500 19.05	1.7500 44.28	0.6250 15.88	0.0625 1.59	1.0000 25.40	0.138 3.46

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lbf) (N)	Static C _s (lbf) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.982 50.00	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2996 11548	1025 4061	0.28 0.13

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7612™ and larger is +.0000-.0006 (+.0000-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473431
Innendurchmesser	19.05 mm
Außendurchmesser	25.63 mm
Dicke	15.88 mm
Gewicht	130 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE