

Zubehör

7618-DL-NICE - 7618-DL-NICE

https://www.123kugellager.ch/kugellager-gehauselager/gehauselager/zubehor/7618-dl-nice

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 8000 RPM
- THERMALLY STABLE
- SHOCK RESISTANT
- WIDE CASE STANDARD
- SHOCK RESISTANT STANDARD
- IDEALY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE IN OPEN AND SEaled VERSIONS
- EXTENDED INNER RING WITH KEY GROOVES
- ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED
- RECOMMENDED FOR APPLICATIONS WHERE EXACTLY SPECIFIED DIMENSIONS AND SUPERIOR QUALITY ARE NECESSARY

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7618™ Ø	1.1250 28.58	2.5246 64.63	0.7500 19.05	0.0625 1.59	1.872 42.47	0.190 4.83

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W (lb) (kg)
0.065 1.65	2.766 70.25	1.417 35.99	0.605 15.37	0.261 6.63	1/4-28	0.035 0.89	5360 23852	2620 11659	0.80 0.36

ⓐ When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
 ⓑ Tolerance for 7613™ and larger is +.0000/-0.0006 (+.0001/-0.15)
 Ⓒ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 Ⓓ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

PRODUKTMERKMALE

Marke	NICE
N° Ean13	3616060473493
Innendurchmesser	28.58 mm
Außendurchmesser	42.47 mm
Dicke	19.05 mm
Gewicht	360 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE