

Gelenkköpfe SI FSX-05-4-DUNLOP - FSX-05-4-DUNLOP

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/si/fsx-05-4-dunlop>

FEMALE ROD ENDS

DUNLOP

FSX SERIES

Description:
FSX series is for 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, heat treated, zinc plated and clear trivalent passivate. Inner Ring: Steel 670M20, zinc plated and clear trivalent passivate and stainless steel 304C. Liner: High strength PTFE bronze mesh composite. Ball: 100Cr6 heat treated, polished and electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to +260°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specification:
ELV & RoHS compliant

Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Strength PTFE Composite

Temp Range: -200°C to +260°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-05-4		1/4	5/16 UNF	0.437	0.344	1.000	1.375	0.750	0.437	25500

Interchange table

Dunlop	Aurora	Fluor
FSX-M (Metric)	AM-M-T and AG-M-T	GUSW
FSX (Imperial)	AM-T and AG-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060556301
Innendurchmesser	6.35 mm
Außendurchmesser	25.4 mm
Dicke	11.0998 mm
Typ	SI
Gewinde	Rechtsgewinde
Schmierung	NA
Statische Belastung	25.5 kN
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE