

# Winkelgelenke SA FSLX-M08-6-DUNLOP - FSLX-M08-6-DUNLOP

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/fslx-m08-6-dunlop>

**FEMALE ROD ENDS** **DUNLOP**



**FSLX SERIES**

**Description:**  
FSLX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate  
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated  
Liners: High Strength PTFE Composite

**Features:**  
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

**Temperature Range:**  
-200°C to +240°C

**Possible Applications:**  
Motorsport and heavy industrial mechanical applications.

**Specification:**  
ELV & RoHS compliant

**Housing:** Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate

**Inner Ring:** Steel 670M20, Zinc Plated and Clear Trivalent Passivate

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

**Liners:** High Strength PTFE Composite

**Temp Range:** -200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-M08-6		6	M8x1.25	12	9.00	24	26	16	13	25500

**Interchange table**

Dunlop	Aurora	Fluro
FSLX-M (Metric)	AM-M-T and AG-M-T	GUSW
FSLX (Imperial)	AM-T and AG-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060558800
Innendurchmesser	6 mm
Innendurchmesser	0.236" inch
Außendurchmesser	24 mm
Außendurchmesser	0.945" inch
Dicke	12 mm
Dicke	0.472" inch
Typ	SA
Gewinde	Linksgewinde
Schmierung	NA
Statische Belastung	25.5 kN
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE