


Winkelgelenke SA FSLX-M10-8-DUNLOP - FSLX-M10-8-DUNLOP

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/fslx-m10-8-dunlop>

FEMALE ROD ENDS **DUNLOP**



FEMALE ROD ENDS

FSX SERIES

Description:
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate
Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C

Features:
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to + 240°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specification:
ELV & RoHS compliant

Housing:	Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate	Balls:	Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Inner Ring:	Steel 670M20, Zinc Plated and Clear Trivalent Passivate	Liners:	High Strength PTFE Composite
		Temp Range:	-200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-M10-R	FSLX-M10-L	8	M10x1.50	14	10.50	28	43	20	17	34800

Interchange table

Dunlop	Aurora	Fluro
FSLX-M (Metric)	AM-M-T and AG-M-T	GUSW
FSLX (Imperial)	AM-T and AG-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060558831
Innendurchmesser	8 mm
Außendurchmesser	28 mm
Dicke	14 mm
Typ	SA
Gewinde	Linksgewinde
Schmierung	NA
Statische Belastung	34.8 kN
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE