

Gelenkköpfe SI

FSX-M20-C-DUNLOP - FSX-M20-C-DUNLOP

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/si/fsx-m20-c-dunlop>

FEMALE ROD ENDS



FSX SERIES

Description:
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate.
Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate.
Ball: 100Cr6 Heat Treated, Polished and Electroless Nickel Plated and Stainless Steel 440C.

Features:
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to +240°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specifications:
ELV & RoHS compliant

Notes:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate.
Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate.
Ball: 100Cr6 Heat Treated, Polished and Electroless Nickel Plated and Stainless Steel 440C.
Temp Range: -200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-M20C		20	M20x1.50	25	18.00	50	77	33	32	9300

Interchange table

Dunlop	Aurora	Fluro
FSX-M (Metric)	AW-M-T and AD-M-T	GUSW
FSX (Imperial)	AW-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUKTMERKMALE

Marke	DUNLOP
N° Ean13	3616060559951
Innendurchmesser	20 mm
Innendurchmesser	0.787" inch
Außendurchmesser	50 mm
Außendurchmesser	1.969" inch
Dicke	25 mm
Dicke	0.984" inch
Typ	SI
Gewinde	Rechtsgewinde
Schmierung	NA
Statische Belastung	93.5 kN
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE