

**Wellenfedern (rundraht)**  
**WSRW-111.13-5-2.79 - WSRW-111.13-5-2.79**

<https://www.123kugellager.ch/zubehor/unterlegscheibe/wellenfedern-rundraht/wsrw-111.13-5-2.79>

Do = Outside diameter (max) (mm)  
Di = Inside diameter (min) (mm)  
t = Thickness (mm)  
H = Free height approx.  
H1 = Load at height  
L1 = Load at L1 (+/-15% Newton)  
DB = Bearing's outside diameter  
Dh = Free fit in hole diameter  
Dr = Free fit over hole diameter  
N/Wx = Number of waves  
Pf = Load at flat (approx.)  
d = Wire diameter



Wave Springs - Round Wire

Part Number	Wx	Lo (mm)	L1 (mm)	Dr (mm)	Dh (mm)	d (mm)	P1 (N)
RW-0437	5	6,10	4,75	103,20	111,13	2,79	1558

**PRODUKTMERKMALE**

Marke	GEN
Anzahl der Wellen	5
Freie Höhe	6.1 mm
Verpackung	1
Höhe bei Belastung	4.75
Spiel auf dem Durchmesser der Achse	103.2 mm
Opera in einer Wohnung mit einem Durchmesser von	111.13 mm
Durchmesser des Fadens	2.79 mm

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE