


## Stehlagereinheiten / Flanschlagereinheiten 2 loch P2BC-35M-CPSS-DFH-SKF - P2BC-35M-CPSS-DFH-SKF

<https://www.123kugellager.ch/kugellager-gehauselager/gehauselager/stehlagereinheiten-flanschlagereinheiten-2loch/p2bc-35m-cpss-dfh-skf>

<b>Données de calcul</b>			
Charge dynamique de base	C	21.8	kN
Charge statique de base	C <sub>0</sub>	15.5	kN
Limite de fatigue	P <sub>0</sub>	0.655	kN
Compliance with standard			Not standardised
Matériau			Composite for the SKF Food Line
Sealing solution			Gutter seals
<b>Dimensions</b>			
			
d		35	mm
A		40	mm
A <sub>1</sub>		40	mm
A <sub>2</sub>		68.6	mm
B		34.9	mm
B <sub>1</sub>		6	mm
B <sub>2</sub>		33.8	mm
H		47.6	mm
H <sub>1</sub>		30	mm
H <sub>2</sub>		30	mm
J		127	mm
J <sub>1</sub>	max.	130	mm
J <sub>2</sub>	min.	124	mm
L		168	mm
N <sub>1</sub>		17	mm
N <sub>2</sub>		14	mm
F <sub>1</sub>		25.4	mm
<b>Plats de centrage</b>			
G		12	mm
G <sub>1</sub>		0.5	in
<b>Calculation data</b>			
Lining speed		500	rpm
with shaft tolerance H6			

### PRODUKTMERKMALE

Marke	SKF
N° Ean13	7316577856005
Durchmesser der Welle	35 mm
Anzahl der Befestigungen	2
Befestigung	Exzentrischer Klemmring
Befestigungsabstand	127 mm
Material	POLYPROPYLEN FÜR LEBENSMITTEL
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE