

Nadellager BHTM916-JTEKT - BHTM916-JTEKT

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/bhtm916-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|--------|-------------------------|-----------------|--------------------------------------|--|---------------------------|-----------------|
| F _w | D | C | b min. | C ₀ | C _{0r} | Oil lub. | | Caged type | |
| 9 | 16 | 16 | 13.3 | 7.95 | 7.90 | 32 000 | | With open ends | With closed end |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|-------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 8.991 | 9.000 | 15.977 | 15.995 | 12 | 13 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3663952469485 |
| Innendurchmesser | 9 mm |
| Innendurchmesser | 0.354" inch |
| Außendurchmesser | 16 mm |
| Außendurchmesser | 0.63" inch |
| Dicke | 16 mm |
| Dicke | 0.63" inch |
| Gewicht | 12 g |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE