

Nadellager 16MKM2212-JTEKT - 16MKM2212-JTEKT

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/16mkm2212-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|----------|---------------------------|-----------------|------------------|
| F_w | D | C | b min. | C_0 | C_{10} | Oil lub. | Caged type | | |
| | | | | | | | | | |
| 16 | 22 | 12 | 9.3 | 7.80 | 9.80 | 22 000 | With open ends | With closed end | |
| | | | | | | | | | 16MKM2212 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|----------------------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 15.989 | 16.000 | 21.991 ⁴⁾ | 22.012 ⁴⁾ | 11 | 12 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3663952470290 |
| Innendurchmesser | 16 mm |
| Außendurchmesser | 22 mm |
| Dicke | 12 mm |
| Gewicht | 12 g |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE