

Nadellager NQ16-20-JTEKT - NQ16-20-JTEKT

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/nq16-20-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----------------|----------------|----------------|-------------------------|-----------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | |
| 16 | — | 24 | 20 | 0.3 | 13.1 | 19.1 | 28 000 | NQ16/20 |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | | | |
| | d _a | D _a | r _a | 0.032 | — | | | |
| | max. | max. | max. | | | | | |
| | — | 22 | 0.3 | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3663952477701 |
| Innendurchmesser | 16 mm |
| Außendurchmesser | 24 mm |
| Dicke | 20 mm |
| Gewicht | 32 g |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE