


Zylinderrollenlager NQI25-30-JTEKT - NQI25-30-JTEKT

<https://www.123kugellager.ch/kugellager-gehauselager/zylinderrollenlager/zylinder/nqi25-30-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 ~ 37 mm
With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|----|----|----|-------------------------|-----------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | |
| 29 | 25 | 38 | 30 | 28.9 | 54.3 | 16 000 | — | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | — | | |
| NQI25/30 | | | | 27 | 36 | 0.085 | 0.125 | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3663952482637 |
| Innendurchmesser | 25 mm |
| Innendurchmesser | 0.984" inch |
| Außendurchmesser | 38 mm |
| Außendurchmesser | 1.496" inch |
| Dicke | 30 mm |
| Dicke | 1.181" inch |
| Gewicht | 125 g |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE