

Zylinderrollenlager NA5915-JTEKT - NA5915-JTEKT

<https://www.123kugellager.ch/kugellager-gehauselager/zyylinderrollenlager/zyylinder/na5915-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|----|-----|----|-------------------------|-----------------|--|--------------------|-------------|-----------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | | |
| 85 | 75 | 105 | 40 | 109.0 | 216.0 | 5 400 | — | | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NA5915 | | | | 80 | 100 | 1 | 0.844 | 1.03 | IRM758540 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | JTEKT |
| N° Ean13 | 3663952483931 |
| Innendurchmesser | 75 mm |
| Außendurchmesser | 105 mm |
| Dicke | 40 mm |
| Gewicht | 1030 g |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE