

## Nadelhülsenlager BAM126-IKO - BAM126-IKO

https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bam126-iko

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

Shaft dia. mm (inch)	Identification number		
	Standard	Mass (Ref.) g	Closed end
19.050 ( $\frac{3}{8}$ )	---	---	BAM 126

  

Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. h6 Max.   Min.	Housing bore dia. J7 Max.   Min.	$C$	$C$	$C_0$	rpm	
19.050   $\frac{3}{8}$	25.400   1	9.521   $\frac{3}{8}$	19.050   h6 Max.   Min.	19.037   J7 Max.   Min.	25.412   25.391	5 040	5 650	20 000	---

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173047
Innendurchmesser	19.05 mm
Außendurchmesser	25.4 mm
Dicke	9.52 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE