



Nadelhülsenlager BAM186-IKO - BAM186-IKO

https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhülsenlager/bam186-iko

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end				
28.575 (1 1/8)	—	—	—	—	—	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm					
<i>F_w</i>	<i>D</i>	<i>C</i>	Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	N	N	—
28.575 1 1/8	34.925 1 1/8	9.52 3/8	28.575 28.562 34.939 34.914	34.939 34.914	6 330	8 910	13 000

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173368
Innendurchmesser	28.58 mm
Außendurchmesser	34.93 mm
Dicke	9.52 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE