


Nadelhülsenlager BAM208-IKO - BAM208-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bam208-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g																																									
	Standard	Mass (Ref.) g	Closed end																																																			
31.750 (1 1/4)	---	---	---	---	---	---	---	---	---	---	---	---	---																																									
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions mm(inch)</th> <th colspan="3">Standard mounting dimensions mm</th> <th>Basic dynam. load rating</th> <th>Basic static load rating</th> <th>Allowable rotational speed(*)</th> <th>Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h₈</th> <th>Housing bore dia. J7</th> <th>Shaft dia. h₈</th> <th>C</th> <th>C₀</th> <th>N</th> <th>N</th> </tr> <tr> <th>Max.</th> <th>Max.</th> <th>Max.</th> <th>Max.</th> <th>Min.</th> <th>Max.</th> <th>Min.</th> <th>N</th> <th>N</th> <th>rpm</th> </tr> </thead> <tbody> <tr> <td>31.750 1 1/4</td> <td>38.100 1 1/2</td> <td>12.70 .500</td> <td>2.8</td> <td>31.750 31.734</td> <td>38.114 38.089</td> <td>9</td> <td>100</td> <td>14 700</td> <td>12 000</td> <td>IRB 168</td> </tr> </tbody> </table>														Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynam. load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring	F _w	D	C	Shaft dia. h ₈	Housing bore dia. J7	Shaft dia. h ₈	C	C ₀	N	N	Max.	Max.	Max.	Max.	Min.	Max.	Min.	N	N	rpm	31.750 1 1/4	38.100 1 1/2	12.70 .500	2.8	31.750 31.734	38.114 38.089	9	100	14 700	12 000	IRB 168
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynam. load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring																																													
F _w	D	C	Shaft dia. h ₈	Housing bore dia. J7	Shaft dia. h ₈	C	C ₀	N	N																																													
Max.	Max.	Max.	Max.	Min.	Max.	Min.	N	N	rpm																																													
31.750 1 1/4	38.100 1 1/2	12.70 .500	2.8	31.750 31.734	38.114 38.089	9	100	14 700	12 000	IRB 168																																												

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173405
Innendurchmesser	31.75 mm
Außendurchmesser	38.1 mm
Dicke	12.7 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE