

Nadelhülsenlager BAM710-IKO - BAM710-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bam710-iko>

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

BAM BHAM

Identification number												
Shaft dia. mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g		
11.112 ($\frac{7}{16}$)	—	—	—	—	—	—	BAM 710	8.5	—	—		

Boundary dimensions mm (inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring		
F _w	D	C	b ₂ Max.	Shaft dia. h8 Min.	Housing bore dia. J7 Min.	N	N				
11.112 ($\frac{7}{16}$)	15.875 ($\frac{5}{8}$)	15.88 (0.625)	1	11.112	11.101	15.885	15.867	6 020	7 550	35 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
 Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173528
Innendurchmesser	11.11 mm
Außendurchmesser	15.88 mm
Dicke	15.88 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE