Nadelhülsenlager
BAM77-IKO - BAM77-IKO

https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bam77-iko



IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number: Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
11.112 (7/16)	— —	— —	— —	— —	— —	— —	BAM 77 —	6.2 —	— —	— —

Boundary dimensions mm(inch) F_w	D	C	r_2 Max.	Standard mounting dimensions mm: Shaft dia. h6 Max.	Shaft dia. h6 Min.	Housing bore dia. J7 Max.	Housing bore dia. J7 Min.	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed(*) rpm	Assembled inner ring
11.112(7/16)	15.875(5/8)	11.13(.438)	1	11.112	11.101	15.885	15.867	4 150	4 680	35 000	—

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

123BEARING

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173542
Innendurchmesser	11.11 mm
Innendurchmesser	7/16" inch
Außendurchmesser	15.88 mm
Außendurchmesser	5/8" inch
Dicke	11.13 mm
Dicke	0.438" inch
Verpackung	1

kontakt@123kugellager.ch
+49 (0) 800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE