


# Nadelhülsenlager BAM910-IKO - BAM910-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bam910-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
14.288 ( $\frac{9}{16}$ )	—	—	—	—	—	—	—	<b>BAM 910</b>	10.8	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. h8		Housing bore dia. J7		$C$	$C_0$	rpm	
			Max.	Min.	Max.	Min.	N	N		
14.288 ( $\frac{9}{16}$ )	19.050 ( $\frac{3}{4}$ )	15.881 (525)	14.288	14.277	19.062	19.041	7 050	9 910	30 000	—

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952173627
Innendurchmesser	14.29 mm
Innendurchmesser	9/16" inch
Außendurchmesser	19.05 mm
Außendurchmesser	3/4" inch
Dicke	15.88 mm
Dicke	5/8" inch
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE